



MIT
Made in Taiwan

研磨機
Spring
End
Grinding
Machine



HDG-660-1

<1.1°

立式磨床
Down Feed

研磨模式
Grinding Mode

左右移動
Horizontally Moving

集塵機
Dust Collector

選購品 Optional

砂輪規格(公釐)
Grinding Wheel Dimension(mm)

OD. Ø660 mm
ID. Ø150 mm

砂輪數目
Grinding Wheel NO.

1

+ Features

- 單頭手試磨台
Spring Sample Grinding
- 油壓設備
Hydraulic
- 全油壓設計
Hydraulic system design
- 彈簧首樣研磨·快速方便
First trial spring sample grinding. Fast and convenient
- 油壓式橫移台·增加研磨效率
Hydraulic system sway platform. Enhance grinding efficiency
- 油壓式夾持·省時省工
Hydraulic system gripper. Fast and easy to use
- 數位計時設定·研磨時間更加準確
Digital timer. Grinding time more specific



HDG-660-1(油壓)

線徑範圍(公釐) Wire Capacity(mm)	Ø 3.0 ~ Ø 20.0 mm	機臺本體尺寸(公釐) Machine Body Dimension(mm) 不含螢幕與電控箱 Electronic Control Box And Screen Excluded	長 Length	1700 mm
彈簧最大外徑(公釐) Max. Spring O.D.(mm)	Ø 310 mm		深 Depth	1600 mm
彈簧長度範圍(公釐) Spring Length(mm)	30 ~ 200 mm		高 Height	2000 mm
切削力 Cutting Ability (mm³/sec)	3 ~ 14 mm³/sec	機臺安全操作 佔地面積(公釐) Safety Operation Location Area(mm)	長 Length	5700 mm
生產速度(條/分) Production Speed(pcs/min)	手動操作 Manual Operation		深 Depth	5700 mm
砂輪轉速(每分鐘轉速) Grinding Wheel Rate(rpm)	1000	機臺重量(公斤) Machine Weight(kgs)	1360 kgs	